

A Fusion of the Art and Science of Light

**SPECIFICATIONS :**

model: CFLX  
 primary power: 120V, 277V  
 compliance: UL Listed  
 control: dimming compatible  
 dimensions: 4'6" to 7'6"  
 lamp color(s): see color chart on Details sheet  
 date: August 20, 2010

**FEATURES :**

CFLX cold cathode has features that are similar to ACL's B100 and B200, yet is easier to install, resulting in significant cost savings for field installation labor. CFLX has qualities of conventional fixtures in that each fixture is shipped separately ready to install. The fixtures are easily daisy-chained, with standard electrical fittings and connectors that are accessed through a sliding door. CFLX does not require costly installation of conduit, remote transformers and assess panels.



Application Concept Photos



© 2010 Architectural Cathode Lighting, Inc.

CATHODE CFLX  
 CUT SHEET

Project Name \_\_\_\_\_ Date \_\_\_\_\_ Linear Feet \_\_\_\_\_ Qty \_\_\_\_\_

**SPECIFICATION CODE:** Note: For a variation (custom) of this product contact ACL to request a variation number and information.

CF	S01	DR	Color (s)	Primary	Dim-able	S
Product	Standard	Environment	Color (s)	Primary	Dim-able	Mount
CFLX Standard Output Cold Cathode	S01	DR - Dry	See Chart (1)	120V 277V	DI - Dim ND - Non Dim	S - Surface

(1) For multiple selections place a comma after each selection.

**ACL INC.**  
 Architectural Cathode Lighting, Incorporated  
[cathodelighting.com](http://cathodelighting.com)

5301 Pacific Boulevard  
 Huntington Park California 90255 USA  
 Telephone 323.581.8800  
 Fax 323.581.7971  
[info@cathodelighting.com](mailto:info@cathodelighting.com)