

A Fusion of the Art and Science of Light

SPECIFICATIONS:

model: SL01 / SL02 / SL03 / SL04

primary power: 120V, 1.0 AMPS, 277V special order

compliance: UL Listed

control: dimming compatible

finish: Clear Anodized Aluminum

dimensions: 4'6", 5'0", 5'6", 6'0", 6'6"

lamp color(s): See color chart on Details sheet.

date: November 3, 2008

FEATURES:

A fresh and creative way to illuminate an interior, Streamlites Cold Cathode lamps have end to end illumination, and are available in several standard lengths and colors. Lamps are mounted to an armature, with various methods for integrating the power supply. Streamlites can be suspended from ceilings, mounted to walls, installed in coves, freestanding and more.

Streamlites express a new and exciting language of hardware that transforms into elegant structures supporting the cathode lamps with minimalist sensibility. This luminaire offers unlimited possibilities that are both classic and timeless.



© 2008 Architectural Cathode Lighting, Inc.

STREAMLITES CUT SHEET

Project Name _____ **Date** _____ **Quantity** _____
SPECIFICATION CODE: Note: For a variation (custom) of this product contact ACL to request a variation number and information.

SL	—	—	—	—	CAA	—	—	DI	—
Product	Standard	Environment	Color	Finish	Primary	Dim-able	Dimensions		
SL-Streamlites (Cold Cathode)	S01 (1) S02 (1) S03 (1) S04 (1)	DR - Dry DP - Damp WT - Wet (2)	See Chart (2)	CAA (Clear Anodized Aluminum)	120V 1A 277V (2)	DI - Dim	4'6" to 6'6" (in increments of 6")		

(1) Power supply option: S01 - Armature Mount, S02 - Ceiling Mount, S03 - Remote, S04 - Remote Pendant.
 (2) Special order, contact ACL for information.
 (3) For multiple selections place a comma after each selection.

 **ACL INC.**
 Architectural Cathode Lighting, Incorporated

cathodelighting.com

5301 Pacific Boulevard
 Huntington Park California 90255 USA
 Telephone 323.581.8800
 Fax 323.581.7971
info@cathodelighting.com